

Cine Tape **OSD** (on screen display) with UHF video transmitter and **RD** (remote display) Units



O.S.D.



OSD at 2 * font size



R.M.

The OSD and RD units plug into the accessory connector on the Cinematography Electronics Cine Tape.

Video from the video assist passes through the OSD to the onboard Monitor. The Cine Tape focus distance reading then shows as an overlay on the assist picture.

This readout can be positioned anywhere on the screen and set to different font sizes.

For hand held, steadycams and cranes, the inbuilt UHF video transmitter can also send the Cine Tape reading as an overlay .

The OSD is aluminum and measures 50*40*30 mm (2*1.75*1.25 in) plus BNC's. weighing 110gm, (4oz).

The RD remote display has large bright red LEDs for displaying the Cine Tape reading on the other side of the camera. It is made from plastic and measures 57*65*35 mm (2.5*2.25*1.4 in), weighing 80 gm, (3 oz).

SYNCCINE P/L **ACN : 006 501 220**
DESIGNERS AND MANUFACTURERS OF QUALITY
COMPUTER CONTROLLED CAMERA ACCESSORIES

15 MacPherson St Nth Carlton 3054
Victoria Australia

Mobile **61 409 380 587**
Email: **info@sync:ne.com**
Web: **www.sync:ne.com**

